

# Dynastraight® Flapper

## Air-Powered Abrasive Finishing Tool

**ABRASIVE CAPACITY**

**ABRASIVE FLAP WHEELS**  
Up to 3" (76 mm) diameter

**For Polishing Insides of Pipe and Tubing; Excellent for Light Deburring**

- Remove rust, oxide and scale; clean welds, remove paint and surface condition using abrasive flap wheels.
- Adjustable speed, lever throttle, front exhaust.

### Model 51130 18,000 RPM, .5 hp

- Includes 51029 Flap Wheel Adapter.
- Shown with optional 90831 abrasive flap wheel, 2-1/2" dia. x 1" wide.

### Model 51301 18,000 RPM, .5 hp

- Includes 1/4" collet.



Model 51130

Wheel Sold Separately



**Gearless**



### Model 51134 18,000 RPM, 8" Extension, .5 hp

- Includes 51116 Adapter.
- Shown with optional 90831 abrasive flap wheel, 2-1/2" dia. x 1" wide.

### Model 53501 18,000 RPM, 8" Extension, .5 hp

- Includes 1/4" collet.



Model 51134

Wheel Sold Separately



**Gearless**

**IMPORTANT:** Speed of tool must not exceed maximum operating speed of accessory. Always wear eye, face and body protection.

Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
51130	.5 (373)	18,000	81 dB(A)	30 (850)	3/8 (10)	1/4" NPT	5/16"-24 Female	1.8 (0.8)	7 (178)	1-3/4 (44)
51134	.5 (373)	18,000	75 dB(A)	30 (850)	3/8 (10)	1/4" NPT	5/16"-24 Female	3.4 (1.5)	17-1/8 (435)	1-7/8 (48)
51301	.5 (373)	18,000	81 dB(A)	24 (680)	3/8 (10)	1/4" NPT	5/16"-24 Female	1.5 (0.7)	7 (178)	1-7/8 (48)
53501	.5 (373)	18,000	75 dB(A)	30 (850)	3/8 (10)	1/4" NPT	—	3.2 (1.5)	17-7/8 (454)	1-7/8 (48)

Tune-Up Kit: No. 95600 (Extension Models – No. 96007) (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

# Lightweight Dynastraight® Plus

## Air-Powered Abrasive Finishing Tool

**Built-In Holder for 3M Roloc and Roloc+ Products**

### Model 13120 3,200 RPM, .4 hp

### Model 13121 5,000 RPM, .4 hp

- Includes 51115 Roloc Adapter Assembly.
- Has built-in speed control, rear exhaust, lever throttle.
- Mount optional abrasive directly to tool.
- Accepts flap brushes and wheels, Cut 'n Polish wheels, Clean 'n Strip® wheels, coated abrasive discs, Scotch-Brite® discs.



Model 13120

Wheel Sold Separately

Roloc+, Roloc, Clean 'n Strip, and Scotch-Brite are registered trademarks of 3M Company.

Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Holder Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
13120	.4 (298)	3,200	81 dB(A)	22 (623)	3/8 (10)	1/4" NPT	Female Roloc	1.8 (.8)	8-1/2 (216)	1-5/8 (40)
13121	.4 (298)	5,000	84 dB(A)	22 (623)	3/8 (10)	1/4" NPT	Female Roloc	1.8 (.8)	8-1/2 (216)	1-5/8 (40)

Tune-Up Kit: No. 96173 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

