## **Rolling Pin Sander**

Air-Powered Abrasive Finishing Tool

## PNEUMATIC WHEEL 3-1/4" dia. x 7" long (83 mm dia. x 178 mm long)

### **For Sanding and Finishing on Contoured Shapes**

### Model 58050 3,200 RPM, .4 hp

- Unique offset handle to control torque.
- Includes 94434 Pneumatic Wheel, 3-1/4" dia. x 7" long. Wheel inflates to 20 PSI max.
- Designed for use with coated abrasive and non-woven nylon belts.





Model	Motor	Motor	Sound	Maximum Air Flow	Hose I.D. Size	Air Inlet	Tool	Weight	Length	Height
Number	hp (W)	RPM	Level	SCFM (LPM)	Inch (mm)	Thread	Thread	Pound (kg)	Inch (mm)	Inch (mm)
58050	.4 (298)	3,200	82 dB(A)	24 (668)	3/8 (10)	1/4" NPT	5/8"-11 male	5 (2.3)	17-3/4 (452)	

Tune-Up Kit: No. 96174 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

### **Mini-Dynisher**

### Air-Powered Abrasive Finishing Tool

# PNEUMATIC WHEELS Up to 5" (127 mm) diameter

#### **Achieves Superior In-Line Finishes on Metal**

 Powers optional Dynacushion® pneumatic wheel. Finish virtually any shape, contour or material, including stainless steel, aluminum, carbon steel, copper, brass, plastic, fiberglass, composites, wood, etc.

### Model 13301 950 RPM, .4 hp

 Ideal for use with optional 94507 Dynacushion® pneumatic wheel (3-1/4" dia. x 3" wide).

#### Model 13300 3,200 RPM, .4 hp

- Ideal for use with optional 94507 Dynacushion® pneumatic wheel (3-1/4" dia. x 3" wide).
- Shroud allows for up to 4-1/2" diameter accessories.

### **13310 Versatility Kit**

 13300 Mini-Dynisher®; 94507 Dynacushion® pneumatic wheel (3-1/4" dia. x 3" wide); 94465 Wheel Inflation Tool; ceramic coated aluminum oxide belt and medium grade non-woven nylon belt.



Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Wheel Arbor Diameter	Hose I.D. Size	Air Inlet Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
13300	.4 (298)	3,200	80 dB(A)	21 (595)	5/8"	1/4 (6)	1/4" NPT	2.8 (1.3)	10 (254)	7 (178)
13301	.4 (298)	950	81 dB(A)	21 (595)	5/8"	1/4 (6)	1/4" NPT	3.4 (1.5)	10 (254)	7 (178)

Tune-Up Kit: No. 96174 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

