

# DynaLocke®

## Air-Powered Dual-Action Sander

**ABRASIVE CAPACITY**

**ABRASIVE DISCS**  
3" (76 mm), 3-1/2" (89 mm),  
5" (127 mm) and 6" (152 mm)  
diameter

### Combination Disc Sander and Random Orbital Sander

- 12,000 RPM DynaLocke® is truly "two tools in one," easily changing from a rotary Disc Sander to Random Orbital Sander with the flip of a switch.
- Ideal for metal applications; great on composite materials. Excellent for automotive work, such as paint stripping and blending. Also utilized for leveling glue seams on Corian® and other solid surfaces.
- Switch is recessed within tool grip to prevent accidental engaging.

#### Non-Vacuum

##### Model 58460 3" Diameter

- Includes low profile, premium urethane sanding pad.

##### Model 58465 3-1/2" Diameter

- Includes low profile, premium urethane sanding pad.

##### Model 58430 5" Diameter


- Includes low profile, premium urethane sanding pad.

##### Model 58435 6" Diameter


- Includes low profile, premium urethane sanding pad.



**Rotary Motion**  
For Stripping and Blending



**3/16" (5 mm) Dia. Random Orbit**  
For Swirl-Free Finishes



#### Self-Generated Vacuum

- Self-Generated Vacuum models are ready for connection to optional portable dust collection system (see page 156).
- Tool has 1-1/4" outside diameter vacuum port, allowing increased air flow.
- Designed to vacuum in random orbital mode only.



##### Model 58461 3" Diameter

- Includes low profile, premium urethane sanding pad.

##### Model 58466 3-1/2" Diameter

- Includes low profile, premium urethane sanding pad.

##### Model 58431 5" Diameter

- Includes low profile, premium urethane sanding pad.

##### Model 58436 6" Diameter

- Includes low profile, premium urethane sanding pad.



DynaLocke® is ideal for leveling glue squeeze on solid surfaces.

Corian is a trademark of DuPont

Model Number	Motor hp (W)	Motor RPM	Pad Dia. Inch (mm)	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
58460	.45 (336)	12,000	3 (76)	78 dB(A)	23 (651)	1/4 (6)	1/4" NPT	5/16"-24 Female	2.35 (1.0)	10-5/16 (263)	5-3/8 (137)
58461	.45 (336)	12,000	3 (76)	78 dB(A)	23 (651)	1/4 (6)	1/4" NPT	5/16"-24 Female	2.35 (1.0)	10-5/16 (263)	5-3/8 (137)
58465	.45 (336)	12,000	3-1/2 (89)	78 dB(A)	23 (651)	1/4 (6)	1/4" NPT	5/16"-24 Female	2.35 (1.0)	10-5/16 (263)	5-3/8 (137)
58466	.45 (336)	12,000	3-1/2 (89)	78 dB(A)	23 (651)	1/4 (6)	1/4" NPT	5/16"-24 Female	2.35 (1.0)	10-5/16 (263)	5-3/8 (137)
58430	.45 (336)	12,000	5 (127)	82 dB(A)	23 (651)	1/4 (6)	1/4" NPT	5/16"-24 Female	2.7 (1.2)	11-1/16 (280)	5-1/8 (131)
58431	.45 (336)	12,000	5 (127)	82 dB(A)	23 (651)	1/4 (6)	1/4" NPT	5/16"-24 Female	2.6 (1.2)	11-1/16 (280)	5-1/8 (131)
58435	.45 (336)	12,000	6 (152)	82 dB(A)	23 (651)	1/4 (6)	1/4" NPT	5/16"-24 Female	2.8 (1.3)	11-1/2 (293)	5-1/8 (131)
58436	.45 (336)	12,000	6 (152)	85 dB(A)	23 (651)	1/4 (6)	1/4" NPT	5/16"-24 Female	2.7 (1.2)	11-1/2 (293)	5-1/8 (131)

Tune-Up Kit: No. 98220 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

