

Wet Dynafine®


Air-Powered Wet Orbital Sander

ABRASIVE
CAPACITY**ABRASIVE DISCS**2" (51 mm), 3" (76 mm)
diameter

Ideal for Removing Imperfections in Clearcoat and Gelcoat Paint Systems

Model 57902 13,000 RPM

- Features our unique "All-in-One" Misting System. The operator can spray the work surface, then remove the imperfection – all within seconds!
- "All-in-One" Misting System helps flush abrasive to achieve a consistent, repeatable finish.
- Includes 2" and 3" diameter vinyl-face sanding pads. Also accepts hook-face sanding pads, sold separately.
- Ergonomic 7° offset design for greater operator comfort and control.
- Low-vibration design allows operator to comfortably run tool for longer time periods.
- Rear exhaust directs air away from work piece; reduces sound levels.
- Insulated tool housing reduces cold air transmission to the operator.
- Gearless design means no right-angle gears to wear out. Tool life is increased!
- Includes 10' water line with 95962 Male Quick Disconnect (1/8") fitting.
- Tool also includes 94407 Flow-Control Dynaswivel®, for added maneuverability (see page 163).



Rotary Orbit Motion
(All models on page)



Portable Wet Tank Assembly (95990) eliminates the need for a separate hose.



Gearless



The use of a filter-regulator-lubricator will increase tool performance, extend tool life and lessen repair costs (see page 162).



Model 57902



Model 57902

57902 Wet Dynafine® has "All-In-One" Misting System to wet work surface in seconds.



Model 57902

Tool accepts vinyl or hook-face sanding pads in diameters of 2" and 3" (above).

Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
57902	.15 (112)	13,000	65 dB(A)	20 (566)	3/8 (10)	1/4" NPT	1.6 (0.7)	9 (229)	3-3/4 (95)

Tune-Up Kit: No. 96236 (page 192)



FASTTRACK

Portable Wet Tank Assembly: Page 206 • Accessories: Page 159