

3" Diameter Buffers

.25 hp, Air-Powered Buffing Tool

For Repair of Sanding Scratches on Clearcoat

ABRASIVE
CAPACITY

**TERRY CLOTH, WOOL,
FOAM BUFFS**
3" (76 mm) diameter

Model 57550 3" Diameter, 2,400 RPM

- Excellent for buffing and polishing fiberglass, plastics and other materials.
- Includes 50125 rigid 3" backing pad, 90027 Terry Cloth Pad and 90028 Wool Pad.
- Low profile housing; rear exhaust; lever throttle.
- Shown with optional 94300 Dynaswivel® and optional 94990 Coupler/Plug Assembly (see page 161).




Model 57550



Model 57550

57550 Palm-Style Buffer utilized on a solid surface sink bowl.




Rotary Orbital Motion



Use Dynabrade Finesse Sanding Cream and Dynabrade Glaze to achieve a superior high gloss finish after compounding.

Model 57553 Versatility Kit

- Efficiently repair dust nibs and scratches on clear coat.
- Quick, simple spot repair on painted surfaces.
- Mini Random Orbital Sander; 3" Buffer; 3-1/2" Disc Sander.
- Includes: 2,400 RPM basic tool; 54476 Mini-Orbital Head; 3" backing pad; 1-1/4" and 3-1/2" dia. vinyl-face pads; 3" dia. terry cloth bonnet, wool bonnet and foam "flat face" pad; 95723 Dynabrade Finesse-It Creme; 95727 Dynabrade Glaze, sample discs and sample abrasive pack. (14 mm and 19 mm wrenches also included; not shown.)



3/16" (5 mm) Dia. Orbit
(with 54776 Head Attached)



Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
57550	.25 (186)	2,400	82 dB(A)	18 (510)	1/4 (6)	1/4" NPT	1/4"-20 Male	1.9 (.9)	5-3/8 (137)	4-1/4 (108)

Tune-Up Kit: No. 96107 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

Roloc is a registered trademark of 3M Company



FASTTRACK

Polishing Buffs: Page 179 • Accessories: Page 159