

Straight-Line Buffer

.4 hp and .7 hp, Air-Powered Models

ABRASIVE CAPACITY
VARIOUS BUFFING AND POLISHING ACCESSORIES

Excellent for Buffing and Polishing Fiberglass, Plastics and Other Materials

Straight-Line, Rear Exhaust

- Shown with optional 95749 Mandrel (1/2") and optional 90024 Cotton Buff Wheels (4" dia. x 1/2" wide).
- Planetary gear allows tool to run at proper speed under load to achieve desired finish.

.4 hp, 1/4" Collet

Model 51200 950 RPM

Model 51201 3,200 RPM

Model 51202 5,000 RPM

.4 hp, 6 mm Collet

Model 51203 950 RPM

Model 51204 3,200 RPM

Model 51205 5,000 RPM

.7 hp, 1/4" Collet

Model 52100 950 RPM

Model 52101 3,400 RPM

Model 52102 4,500 RPM

.7 hp, 6 mm Collet

Model 52103 950 RPM


Model 52104 3,400 RPM

Model 52105 4,500 RPM



Model 52101

Mandrel and Wheels Sold Separately



Rotary Orbital Motion
(All models on page)

Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
51200/51203	.4 (298)	950	82 dB(A)	23 (651)	1/4 (6)	1/4" NPT	3/8"-24 Male	2.1 (1.0)	10-3/8 (264)	1-5/8 (40)
51201/51204	.4 (298)	3,200	81 dB(A)	23 (651)	1/4 (6)	1/4" NPT	3/8"-24 Male	1.8 (0.8)	9-1/8 (232)	1-5/8 (40)
51202/51205	.4 (298)	5,000	84 dB(A)	23 (651)	1/4 (6)	1/4" NPT	3/8"-24 Male	1.8 (0.8)	9-1/8 (232)	1-5/8 (40)
52100/52103	.7 (522)	950	84 dB(A)	34 (957)	3/8 (10)	1/4" NPT	1/2"-20 Male	3.6 (1.6)	12-1/2 (318)	1-7/8 (48)
52101/52104	.7 (522)	3,400	82 dB(A)	35 (977)	3/8 (10)	1/4" NPT	1/2"-20 Male	2.7 (1.2)	9-1/2 (241)	1-7/8 (48)
52102/52105	.7 (522)	4,500	82 dB(A)	35 (977)	3/8 (10)	1/4" NPT	1/2"-20 Male	2.7 (1.2)	9-1/2 (241)	1-7/8 (48)

Tune-Up Kit: .4 hp Tools – No. 96173; .7 hp Tools – No. 96260 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

Electric Buffer

Electric Large Diameter Polishing Tool

ABRASIVE CAPACITY
POLISHING PADS AND BUFFS
6" - 8" (152 mm - 203 mm) dia.

Achieve Fine Finish on a Variety of Surfaces

Model 51610

120 V (AC), 5/8"-11 Male Thread

- 9 amp motor, 0-3,000 RPM (variable RPM dial).
- Double-insulated (Class II) housing, 8 ft. (2.44 m) flexible cord, and built-in tool rest.
- Shown with optional 50853 Backup Pad and optional 90082 Polishing Pad.



Model 51610

120 V (AC)



Model Number	Motor RPM	Maximum Watts Out	Voltage	Current Amps	Phase	Frequency	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
51610	0 - 3,000	835	120 V (AC)	9	1	60 Hz	4.9 (2.2)	16-5/8 (423)	5 (127)

