

# .4 hp Die Grinders

## Straight-Line, Gearless, Rear Exhaust

**ABRASIVE CAPACITY**  
CARBIDE BURRS, ROTARY FILES, MOUNTED POINTS, WHEELS AND DISCS

### High Quality Air-Powered Die Grinders

- Gearless motors decrease downtime and lessen repair expense when compared to geared tools.
- Features standard muffler for more compact design.

**Model 52325**  
25,000 RPM, 1/4" Collet

**Model 52326**  
25,000 RPM, 6 mm Collet

**Model 52327**  
30,000 RPM, 1/4" Collet

**Model 52328**  
30,000 RPM, 6 mm Collet

**Model 52345**  
30,000 RPM, 1/8" Collet

**Model 52341**  
30,000 RPM, 1/8" Collet

- Model 52341 includes 94994 Overhose Assembly.



Model 52325



**Gearless**



Optional 94994 Overhose Assembly may be used to further reduce noise levels by as much as 5 dB(A). Overhose redirects exhaust away from operator and workpiece. Air line sold separately. (See page 157.)



Model Number 1/4" / 6 mm	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
52325 / 52326	.4 (298)	25,000	81 dB(A)	22 (623)	1/4 (6)	1/4" NPT	—	0.8 (0.4)	5-3/4 (146)	1-5/8 (41)
52327 / 52328	.4 (298)	30,000	83 dB(A)	23 (651)	1/4 (6)	1/4" NPT	—	0.8 (0.4)	5-3/4 (146)	1-5/8 (41)
52345 / —	.4 (298)	30,000	83 dB(A)	23 (651)	1/4 (6)	1/4" NPT	—	0.8 (0.4)	5-3/4 (146)	1-5/8 (41)
52341 / —	.4 (298)	30,000	83 dB(A)	23 (651)	1/4 (6)	1/4" NPT	—	0.8 (0.4)	5-3/4 (146)	1-5/8 (41)

Tune-Up Kit: No. 96049 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

# .4 hp Die Grinders

## Straight-Line, Gearless, Front Exhaust

**ABRASIVE CAPACITY**  
CARBIDE BURRS, ROTARY FILES, MOUNTED POINTS, WHEELS AND DISCS

### High Quality Air-Powered Die Grinders

- Gearless motors decrease downtime and lessen repair expense when compared to geared tools.

**Model 52200**  
25,000 RPM, 1/4" Collet

**Model 52230**  
25,000 RPM, 6 mm Collet

**Model 52202**  
30,000 RPM, 1/4" Collet

**Model 52232**  
30,000 RPM, 6 mm Collet



The use of a filter-regulator-lubricator will increase tool performance, extend tool life and lessen repair costs. (See page 162.)



Model 52200



**Gearless**

Model 52200

Model Number 1/4" / 6 mm	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
52200 / 52230	.4 (298)	25,000	75 dB(A)	20 (566)	1/4 (6)	1/4" NPT	—	0.8 (0.4)	5-1/8 (130)	1-5/8 (41)
52202 / 52232	.4 (298)	30,000	88 dB(A)	20 (566)	1/4 (6)	1/4" NPT	—	0.8 (0.4)	5-1/8 (130)	1-5/8 (41)

Tune-Up Kit: No. 96048 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

