DYNABRADE ELECTRIC TOOLS



Reorder No. D11.05

Electric Dynafile II Abrasive Belt Tool

GRIND • DEBURR • BLEND • FINISH • SURFACE CONDITION



- Electric Dynafile® II
 runs coated abrasive and
 non-woven nylon belts, and is
 ideal for countless applications
 on metal, plastic, fiberglass,
 solid surface, stone, glass, etc.
- Grind with contact wheel or platen pad.
 Finish and polish using slack of belt.
- Tool accepts over 20 interchangeable contact arms, for use with belts 1/8" to 3/4" wide x 18" long.
- · Comfortable switch with "lock on" feature.
- · Easily accessible brushes for quick replacement.
- Sanding head pivots 360°, for working in previously inaccessible areas.
- · Reversible side handle for operator comfort.
- Tool is double-insulated for safety, and includes electric cord, 8 feet in length.

Electric Dynafile® II

Model 40610 11,000 RPM

• Tool includes 11203 Contact Arm, for abrasive belts 1/2" wide by 18" long.

Electric Dynafile® II Versatility Kit

Model 40611

Includes 40610 Electric Dynafile® II with 11203
 Contact Arm, and two additional arms (11202 and 11204). Also includes eight abrasive belts of various grits, and an assortment of platen pads.

 All items contained in a durable carrying case.





Contact Arms Included in Versatility Kit:



- Belt Size: 1/4" (6 mm) x 18" (457 mm).
- Enter 5/16" (8 mm) x 3/4" (19 mm) openings.





- Belt Size: 1/2" (13 mm) x 18" (457 mm).
- Grind over contact wheel or platen.



11204	

- Belt Size: 1/4" (6 mm), 5/16" (8 mm)
 OR 1/2" (13 mm) x 18" (457 mm).
- Unique offset design.



			Maximum			Current			Maximum			
N	ımber	RPM	Watts Out	Inch (mm)	Voltage	Amps	Phase	Frequency	SFPM (SMPM)	Pound (kg)	Inch (mm)	Inch (mm)
4	0610	11,000	680	1/8-3/4 (3-19) W x 18-24 (457-610) L	120 V (AC)	6	1	60 Hz	2,520 (768)	5 (2.3)	19 (483)	5.5 (140)



DYNABRADE ELECTRIC TOOLS




Electric Depressed Center Wheel Grinder

FOR 4-1/2" DIAMETER GRINDING WHEELS & ABRASIVE DISCS

- ➤ Powerful 680 W Motor
- ➤ Quick Weld & Stock Removal
- ➤ Heavy Deburring
- ➤ Rust & Scale Removal





- Industrial-quality electric motor rated at 6 amps.
- Easily accessible brush holders allow quick brush replacement (recommended every 150 hours).
- Convenient spindle lock offers fast change of accessory.
- Press-fit design keeps gear in place, to maintain accessory mounting accuracy.
- Locking power switch allows extended use with less operator fatique.
- · Repositioning side handle for left or right hand operation.
- All ball-bearing and needle-bearing construction ensures longer tool durability.



40260 Depressed Center Wheel Grinder offers countless grinding and material removal solutions to a wide variety of industries.



Important: Always use required wheel guard. Never remove wheel guard from tool. Speed of tool must not exceed maximum operating speed of accessory. Never mount bonded grinding wheels. Always wear eye, face and body protection.

Model Number	Maximum Watts Out	Motor RPM	Voltage (AC)	Current Amps	Phase	Frequency	Weight* Pound (kg)	Length Inch (mm)	Height Inch (mm)
40260	680	11,000	120	6	1	60 Hz	4.6 (2.1)	12 (305)	4-1/4 (108)

*Weight includes flanges, side handle and wheel guard, with no wheel attached.

DISTRIBUTED BY:



Visit Our Website: www.dynabrade.com

Email: customer.service@dynabrade.com

Sold Separately

DYNABRADE, INC. • DYNABRADE INTERNATIONAL

8989 Sheridan Drive, Clarence, New York 14031-1419 USA Telephone: (716) 631-0100 • Fax: 716-631-2073 • Int'l Fax: 716-631-2524

DYNABRADE DO BRASIL

Rua Oneda, 632 • Sao Bernardo do Campo • SP – CEP 09895-280 Telephone: 55-11-4390-0133 • Fax: 55-11-4399-1067

DYNABRADE EUROPE S.àr.I.

Zone Artisanale Op Tomm 6 • L-5485 Wormeldange—Haut, Luxembourg Telephone: +352 768 494 1 • Fax: +352 768 495

DYNABRADE INDIA ABRASIVE POWER TOOLS Pvt Ltd.

EL-54, TTC Industrial Area, M.I.D.C. Mahape, Electronic Zone, Navi Mumbai - 400705 Maharashtra, India • Telephone: +91 22 2763 2226 • Fax: +91 22 2763 2228