

DYNABRADE STATIONARY EQUIPMENT

Reorder No. EUR07.13

Downdraft Sanding Tables

ELIMINATE AIRBORNE DUST AND CONTAMINANTS WHILE SANDING

64203

Working Area of
84 cm W x 152 cm L

- Ideal for use non-vacuum, central vacuum, or vacuum ready tools equipped with non-vacuum pads.
- Dual filtration – accepts 1-micron pleated paper filters, 610 mm W x 640 mm L (20" x 25"). (Model 64203 include two filters; model 64204 includes three filters.)
- Each model also includes one 5-micron pre-filter blanket. Pre-filter blanket can be folded in half for clean removal.
- Rhino Linings® coated tabletop surface is durable and anti-slip.
- 127 mm (5") diameter casters allow easy maneuverability of table.
- Two handy storage compartments for tools and accessories.
- Two gas springs support the cover when opened.

64204

Working Area of
91 cm W x 183 cm L



(Arrows Indicate Air Flow)

Specifications

- **Power Source:** Centrifugal fans, direct driven, double inlet, galvanized steel (motor cooled by the air flow).
- **Electric Capacity:** 230 V/50 Hz single phase.
- **Two Paper Filters Available:**
 - 64671: 508 mm W x 635 mm L x 51 mm thick (20" x 25" x 2") standard paper air filter
 - 64672: 508 mm W x 635 mm L x 51 mm thick (20" x 25" x 2").



Model Number	Motor hp (W)	Volts/Hz	Phase	Vacuum Suction	Sound Level	Working Area Width	Working Area Length	Height	Shipping Weight
64203	.75 (550)	230/50	1	1900 CFM	72 dB(A)	84 cm (33")	152 cm (60")	91 cm (36")	130 kg (287 lbs.)
64204	.75 (550)	230/50	1	1900 CFM	72 dB(A)	91 cm (36")	183 cm (72")	94 cm (36")	150 kg (331 lbs.)

Visit our Website for more Tools and Related Accessories



www.dynabrade.com

DYNABRADE EUROPE S.à r.l.

Zone Artisanale • L-5485 Wormeldange-Haut, Luxembourg
Phone: +352 768 494 1 • Fax: +352 768 495

©DYNABRADE, INC., 2007

7/07

DISTRIBUTED BY:

