



# Dynaflex® Contact Arms

## 4" to 14" Workable Reach

- All rubber Contact Wheels are 70 durometer, unless noted.

**See more information  
on Contact Wheels and  
Assemblies on page 256!**

| Part Number   | Comments   | Belt Size<br>(W x L)                         | Contact Wheel Assembly<br>(includes bearing and shaft)   | Platen Pad<br>(see page 29) |
|---|--|--|--|-----------------------------|
| <b>11237, 11238</b><br>Turbine Blade Arm<br> | <ul style="list-style-type: none"> <li>• <b>45 PSIG maximum</b></li> <li>• For use on turbine blades</li> <li>• Reach areas as small as 5/16" wide</li> <li>• 1-1/2" strap polish area</li> </ul>      | 11237:<br>1/4" x 24"<br>11238:<br>1/2" x 24" | 11237: 5/16" dia. x 1/8" wide, steel wheel<br>11238: 1/4" dia. x 3/8" wide, steel (Consists of three 11051 Bearings) | None                        |
| <b>11239</b><br>                             | <ul style="list-style-type: none"> <li>• <b>45 PSIG maximum</b></li> <li>• Heavy-duty steel</li> <li>• Grind in narrow areas</li> </ul>  | 1/2" x 24"                                   | 11068<br>5/16" dia. x 3/8" wide, steel   | 11027<br>1/2" wide;<br>Thin |
| <b>11240</b><br>                             | <ul style="list-style-type: none"> <li>• 9" workable reach</li> <li>• Optional 11024 Steel Platen Pad available</li> </ul>   | 1/2" x 34"                                   | 11078<br>5/8" dia. x 3/8" wide, rubber   | 11025<br>1/2" wide;<br>Soft |
| <b>11241</b><br>                             | <ul style="list-style-type: none"> <li>• 9" workable reach</li> </ul>  | 1/4" x 34"                                   | 11074<br>5/8" dia. x 1/8" wide, rubber   | 11032<br>1/4" wide;<br>Soft |
| <b>11243</b><br>                             | <ul style="list-style-type: none"> <li>• Heavy-duty steel</li> <li>• Grind over contact wheel or platen pad</li> </ul>   | 1/2" x 24"                                   | 11084<br>3/4" dia. x 1/2" wide, rubber   | 11135<br>1/2" wide;<br>Hard |
| <b>11244, 11245</b><br>                       | <ul style="list-style-type: none"> <li>• 14" workable reach</li> <li>• Optional 11024 Steel Platen Pad available</li> </ul>  | 11244:<br>1/2" x 44"<br>11245:<br>1/4" x 44" | 11078<br>5/8" dia. x 3/8" wide, rubber   | 11025<br>1/2" wide;<br>Soft |
| <b>11253, 11254</b><br>Big Wheel Arm<br>    | <ul style="list-style-type: none"> <li>• Grinds and polishes deep slots or narrow grooves</li> </ul>   | 1/4" to 1/2" x 34"                           | 1/4" to 1/2" wide wheels, 2-1/8" to 4-3/4" diameter (specify size)   |                             |
| <b>11255</b><br>Cross Bow Arm<br>          | <ul style="list-style-type: none"> <li>• I.D. polish, deburr or ream with one 180° wrist turn</li> <li>• Deburr leading radius of 1" to 4" round openings</li> <li>• Great for pipe fitters</li> </ul> | 1/2" x 34"                                   | 11078<br>5/8" dia. x 3/8" wide, rubber   | None                        |
| <b>11258</b><br>Stroke Sander Arm<br>      | <ul style="list-style-type: none"> <li>• Blend stainless steel</li> </ul>  | 1/2" x 24"                                   | 11078<br>5/8" dia. x 3/8" wide, rubber<br>11076<br>7/16" dia. x 3/8" wide, steel                                     | 11025<br>1/2" wide;<br>Soft |
| <b>11261</b><br>"The Banana Arm"<br>       | <ul style="list-style-type: none"> <li>• For in-line scratch pattern</li> </ul>  | 1/2" x 24"                                   | 11078<br>5/8" dia. x 3/8" wide, rubber   | 11132<br>1/2" wide          |
| <b>11262</b><br>Offset Arm<br>             | <ul style="list-style-type: none"> <li>• For flat grinding using platen at or near corners and edges of large radiuses</li> <li>• Contact wheel is offset to prevent gouging</li> </ul>                | 1/2" x 24"                                   | 11078<br>5/8" dia. x 3/8" wide, rubber   | 11026<br>1/2" wide;<br>Hard |
| <b>11297</b><br>Guide-Cut Arm<br>          | <ul style="list-style-type: none"> <li>• Guide wheels prevent undercutting</li> <li>• Removes raised material within .020" or less</li> <li>• Use 60 to 80 grit belts</li> </ul>                       | 1/2" x 24"<br>60 to 80 grit                  | 11090<br>5/8" dia. x 3/8" wide, rubber   | None                        |
| <b>11312</b><br>                           | <ul style="list-style-type: none"> <li>• Grind over contact wheel or platen</li> <li>• Heavy-duty applications</li> </ul>  | 1/2" x 24"                                   | 11078<br>5/8" dia. x 3/8" wide, rubber   | 11025<br>1/2" wide;<br>Soft |