.7 hp Drills

Air-Powered Industrial Quality Drills



DYNAJET PAGE 224

AIR LINES PAGE 225

FOR STANDARD DRILL BITS **AND ACCESSORIES NOT INCLUDED**

Pistol Grip, Rear Exhaust Design

Pistol Grip, .7 hp, Rear Exhaust

• Each model includes 3/8" drill chuck and key. • High-torque air motor; slow-speed startup trigger.

· Rubber insulated grip for operator comfort.





Pistol Grip, .7 hp, Rear Exhaust **NEW! Additional Speeds and Chucks!**

• High-torque air motor; slow-speed startup trigger.

· Rubber insulated grip for operator comfort.

Model 53092 500 RPM, 1/2" Keyed Chuck Model 53090 950 RPM, 1/2" Keyed Chuck Model 53093 1,800 RPM, 3/8" Keyed Chuck Model 53094 2,400 RPM, 3/8" Keyed Chuck





Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (L/Min)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Spindle Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
53060	.7 (522)	3,400	81 dB(A)	33 (935)	3/8 (10)	1/4" NPT	1/2"-20 Male	3.2 (1.4)	8-7/8 (224)	6-3/8 (163)
53090	.7 (522)	950	81 dB(A)	33 (935)	3/8 (10)	1/4" NPT	1/2"-20 Male	4.8 (2.1)	10-1/2 (267)	6-3/8 (163)
53091	.7 (522)	950	79 dB(A)	33 (935)	3/8 (10)	1/4" NPT	1/2"-20 Male	3.9 (1.8)	10-1/2 (267)	6-3/8 (163)
53092	.7 (522)	500	76 dB(A)	30 (850)	3/8 (10)	1/4" NPT	1/2"-20 Male	4.9 (2.2)	10-5/8 (270)	6-3/8 (163)
53093	.7 (522)	1,800	73 dB(A)	28 (793)	3/8 (10)	1/4" NPT	1/2"-20 Male	3.2 (1.5)	8-7/8 (224)	6-3/8 (163)
53094	.7 (522)	2,400	74 dB(A)	30 (850)	3/8 (10)	1/4" NPT	1/2"-20 Male	3.2 (1.5)	8-7/8 (224)	6-3/8 (163)
53095	.7 (522)	4,500	82 dB(A)	33 (935)	3/8 (10)	1/4" NPT	1/2"-20 Male	3.2 (1.4)	8-7/8 (224)	6-3/8 (163)
53096	.7 (522)	20,000	86 dB(A)	33 (935)	3/8 (10)	1/4" NPT	3/8"-24 Male	2.4 (1.1)	7 (180)	6-3/8 (163)

Tune-Up Kits: 53060, 53090, 53091, 53095, 53096 - No. 96047; 53092, 53093, 53094 - No. 96466 (page 267)

Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)