

# Pistol Grip Buffer

Accepts 3" Diameter Buffing Accessories



**DYNASWIVEL®**  
PAGE 223

**ACCESSORIES**  
PAGE 222

*Portable Air Tools for the Value-Minded Professional*

**FOR POLISHING BUFFS**  
3" diameter (76 mm)  
SEE PAGE 239

## Model 18068 3/8"-24 Thread

- Operates at 2,500 RPM, ideal for a variety of buffing applications.
- Includes 50126 Hook-Face Backing Pad, for accepting optional buffs and bonnets 3" (76 mm) in diameter (see Versatility Kit on page 189).
- Ergonomic pistol grip design enhances operator comfort.
- To run 92295 RED-TRED® Eraser Disc Assembly, order optional 55066 Adapter (converts 3/8"-24 spindle thread to 5/8"-11 thread).



Model 18068

Model Number	Motor hp (W)	Motor RPM	Pad Dia. Inch (mm)	Sound Level	Max. Air Flow SCFM (LPM)	Spindle Thread	Air Inlet Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
18068	.18 (134)	2,500	3 (72)	80 dB(A)	23 (651)	3/8"-24	1/4" NPT	1.7 (0.8)	5 (128)	6-3/8 (162)
18069	.18 (134)	2,500	4 (102)	80 dB(A)	23 (651)	5/8"-11	1/4" NPT	2.5 (1.1)	5.3 (135)	7 (178)
18072	.18 (134)	2,500	4 (102)	80 dB(A)	23 (651)	M14x2	1/4" NPT	2.5 (1.1)	5.3 (135)	7 (178)

Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

# Dual-Piston Sander

In-Line Sander

*Achieve Consistent Finishes on Large Work Surfaces*

**FOR ABRASIVE SHEETS**  
2-3/4" wide x 17" long (70 mm x 432 mm)  
NOT INCLUDED

## Model 18066

- 2,500 strokes per minute.
- Long board air-powered sander, two-handed operation.
- Accepts 2-3/4" wide x 17" long (70 mm x 432 mm) abrasive sheets.
- Includes rubber backup pad, 2-3/4" wide by 16" long (70 mm x 406 mm), with clips for securing abrasive sheets.



Model 18066

Model Number	Maximum Air Flow SCFM (LPM)	Air Pressure PSIG (Bar)	Air Inlet Thread	Weight Pound (kg)	Stroke Length Inch (mm)	Pad Size Inch (mm)	Paper Size Inch (mm)
18066	14 (396)	90 (6.2)	1/4" NPT	6 (2.7)	1 (25)	2-3/4 x 16 (70 x 406)	2-3/4 x 17-1/2 (70 x 445)