

# Mini-Dynafile® II Contact Arms

## 3" Workable Reach; Exclusive to Mini-Dynafile® II

- All rubber Contact Wheels are 70 durometer, unless noted.

Part Number	Comments	Belt Size (W x L)	Contact Wheel Assembly (includes bearing and shaft)	Platen Pad (see page 29)
15025, 15028 	<ul style="list-style-type: none"> <li>• No platen due to offset design</li> <li>• Grind radiuses</li> <li>• Offset for slack polishing</li> </ul> 	1/4" or 1/2" x 12"	15025: 11093 Wheel, 1" dia. x 3/8" wide, 40 duro rubber 15028: 11080 Wheel, 1" dia. x 3/8" wide, 70 duro rubber	None
15026 	<ul style="list-style-type: none"> <li>• <b>Standard on Model 15003</b></li> <li>• Grind corners, enter grooves</li> </ul> 	1/2" x 12"	11078 5/8" dia. x 3/8" wide, rubber	11026 1/2" wide; Hard
15027 	<ul style="list-style-type: none"> <li>• Sand on both sides of arm</li> <li>• Enter confined areas as small as 1/4"</li> </ul>	1/4" x 12"	11074 5/8" dia. x 1/8" wide, rubber	11033 1/4" wide; Hard
15029 	<ul style="list-style-type: none"> <li>• Grind corners, enter grooves and strap polish</li> </ul> 	1/8" x 12"	11086 1" dia. x 3/8" wide, urethane	None
15030 	<ul style="list-style-type: none"> <li>• <b>45 PSIG maximum</b></li> <li>• Enter channels as narrow as 7/16"</li> </ul> 	1/2" x 12"	11068 5/16" dia. x 3/8" wide, steel	11027 1/2" wide; Thin
15031 	<ul style="list-style-type: none"> <li>• <b>45 PSIG maximum</b></li> <li>• Work on contact wheel or platen pad</li> </ul> 	1/2" x 13"	11070 7/16" dia. x 3/8" wide, rubber	11027 1/2" wide; Thin
15032 	<ul style="list-style-type: none"> <li>• <b>45 PSIG maximum</b></li> <li>• Grind, blend and polish turbine blades</li> </ul>	1/2" x 12"	11332 1/4" dia. x 3/8" wide, steel	None
15033 	<ul style="list-style-type: none"> <li>• <b>45 PSIG maximum</b></li> <li>• Grind, polish turbine blades and other contours</li> </ul>	1/4" x 12"	11342 5/16" dia. x 3/8" wide, rubber	None