

Versatility Grinder Contact Arms

| Part Number | Comments | Belt Size | Contact Wheel Assembly (includes bearing and shaft) | Platen Pad |
|----------------------------|---|--|--|------------------------------|
| 11200 | <ul style="list-style-type: none"> Work on broad areas Leave in-line scratch Blend spot welds | 1/2" x 72" | 11088 5/8" dia. x 3/8" wide, rubber | 11025 1/2" wide |
| 11201 | <ul style="list-style-type: none"> Enter channels as small as 7/16" 2,000 SFPM Maximum | 1/2" x 72" | 11068 5/16" dia. x 3/8" wide, steel | 11027 1/2" wide |
| 11202 | <ul style="list-style-type: none"> Enter 5/16" x 3/4" openings 2,000 SFPM Maximum | 1/4" x 72" | 11074 5/8" dia. x 1/8" wide, rubber | 11032 1/4" wide |
| 11203 | <ul style="list-style-type: none"> Grind over contact wheel or platen Order 11312 for heavy-duty, or 11325 for steel platen version 4,000 SFPM Maximum | 1/2" x 72" | 11078 5/8" dia. x 3/8" wide, rubber | 11025 1/2" wide |
| 11204 | <ul style="list-style-type: none"> Unique offset design Strap polishing is easy 4,000 SFPM Maximum | 1/8", 1/4", 5/16" or 1/2" x 72" | 11080 1" dia. x 3/8" wide, radiused rubber | None |
| 11206 | <ul style="list-style-type: none"> Order 11326 for heavy-duty steel construction version 4,000 SFPM Maximum | 5/8" or 3/4" x 72" | 11282 3/4" dia. x 5/8" wide, rubber | 11109 3/4" wide |
| 11220, 11300, 11301, 11341 | <ul style="list-style-type: none"> Offset design and miniature contact wheels 2" strap polish in offset area; polish turbine blades and other contours 2,000 SFPM Maximum | 11220: 5/8" or 3/4" x 72" All Others: 1/2" x 72" | 11220: 11352 5/16" x 5/8" wide, steel 11300: 11332 1/4" x 3/8" wide, steel 11301: 11068 5/16" x 3/8" wide, steel 11341: 11342 5/16" x 3/8" wide, rubber | None None None None |
| 11280 | <ul style="list-style-type: none"> Grind corners, enter grooves, strap polish "V" shape wheel | 1/8" or 1/4" x 72" | 11086 1" dia. x 3/8" wide, urethane, tapered | None |
| 11286 | <ul style="list-style-type: none"> 11024 Steel Platen available 6-3/4" workable reach 4,000 SFPM Maximum | 1/2" x 78" | 11078 5/8" dia. x 3/8" wide | 11025 1/2" wide |
| 11287 | <ul style="list-style-type: none"> Grind on wheel or platen 5-1/4" reach 4,000 SFPM Maximum | 5/8" or 3/4" x 74-1/2" | 11282 3/4" x 5/8" wide, rubber | 11109 3/4" wide |
| 11314 | <ul style="list-style-type: none"> File round openings as small as 7/16" 2,000 SFPM Maximum | 1/4" x 72" | 11066 5/16" dia. x 1/8" wide, steel | 11034 1/4" wide |
| 11320 Offset Arm | <ul style="list-style-type: none"> For flat grinding using platen at or near corners and edges of large radius round Contact wheel is offset to prevent gouging 4,000 SFPM Maximum | 1/2" x 72" | 5/8" dia. x 3/8" wide, rubber | 11026 1/2" wide |
| 11321 | <ul style="list-style-type: none"> Work on contact wheel or platen pad 2,000 SFPM Maximum | 1/2" x 72" | 11070 7/16" dia. x 3/8" wide, rubber | 11025 1/2" wide |
| 11322 | <ul style="list-style-type: none"> Guide-cut Removes raised material within .020" or less without undercutting | 1/2" x 72" | 11090 5/8" dia. x 3/8" wide, rubber | None |
| 11329 | <ul style="list-style-type: none"> Extra length arm 17" workable reach 4,000 SFPM Maximum | 1/2" x 98" | 11078 5/8" dia. x 3/8" wide, rubber | 11025 1/2" wide |
| 11330 | <ul style="list-style-type: none"> Enter 1/2" x 1/2" openings 2,000 SFPM Maximum | 1/4" x 72" | 11072 7/16" dia. x 1/8" wide, brass | 11034 1/4" wide |
| 11337 | <ul style="list-style-type: none"> Enter channels as narrow as 9/16" 2,000 SFPM Maximum | 1/2" x 72" | 11076 7/16" dia. x 3/8" wide, steel | 11027 1/2" wide |