

# Dynastraight® Flapper

## Air-Powered Abrasive Finishing Tool



COUPLER/PLUG  
PAGE 228

ACCESSORIES  
PAGE 222

*For Polishing Insides of Pipe and Tubing;  
Excellent for Light Deburring*

FOR ABRASIVE FLAP WHEELS  
Up to 3" (76 mm) diameter  
SEE PAGE 282

- Remove rust, oxide and scale; clean welds, remove paint and surface condition using abrasive flap wheels.
- Adjustable speed, lever throttle, front exhaust.




Model 51130

Wheel Sold Separately



### Model 51130 18,000 RPM, .5 hp

- Includes 51029 Flap Wheel Adapter.
- Shown with optional 90831 Abrasive Flap Wheel, 2-1/2" dia. x 1" wide.



Dynaswivel® air line connector is ideal for use with most air tools. It improves tool maneuverability, minimizes operator fatigue and extends hose life. (See page 223.)



### Model 51301 18,000 RPM, .5 hp

- Includes 1/4" collet.

### Model 51134 18,000 RPM, 8" Extension, .5 hp

- Includes 51116 Adapter.
- Shown with optional 90831 Abrasive Flap Wheel, 2-1/2" dia. x 1" wide.



Model 51134

Wheel Sold Separately



**IMPORTANT:** Speed of tool must not exceed maximum operating speed of accessory. Always wear eye, face and body protection.

Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (L/Min)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
51130	.5 (373)	18,000	81 dB(A)	30 (850)	3/8 (10)	1/4" NPT	5/16"-24 Female	1.8 (0.8)	7 (178)	1-3/4 (44)
51134	.5 (373)	18,000	75 dB(A)	30 (850)	3/8 (10)	1/4" NPT	5/16"-24 Female	3.4 (1.5)	17-1/8 (435)	1-7/8 (48)
51301	.5 (373)	18,000	81 dB(A)	24 (680)	3/8 (10)	1/4" NPT	5/16"-24 Female	1.5 (0.7)	7 (178)	1-7/8 (48)

Tune-Up Kit: No. 95600 (51134 – No. 96007) (page 267) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

**HIGHEST QUALITY!**

**FASTEST SHIPPING!**



**FREE ON-SITE DEMOS!**

**BEST SERVICE!**

**Discover The Dynabrade Difference!**

**Dynabrade.com**