

# 3" Dia. Disc Sanders

## .4 hp, .55 hp and .7 hp Models



DISC PADS  
PAGE 242

ACCESSORIES  
PAGE 222

### High-Quality Air-Powered Disc Sanders

#### Right Angle, .4 hp, Rear Exhaust

- Includes 51346 Locking-Type Pad (3" diameter).
- Extended muffler design.

**Model 48530** 12,000 RPM

**Model 48531** 15,000 RPM

**Model 48532** 20,000 RPM



FOR ABRASIVE DISCS  
3" (76 mm) diameter  
SEE PAGE 279



See page 87-88 for  
VACUUM Models!

| Model Number | Motor hp (W) | Motor RPM | Sound Level | Maximum Air Flow SCFM (L/Min) | Hose I.D. Size Inch (mm) | Air Inlet Thread | Tool Thread  | Weight Pound (kg) | Length Inch (mm) | Height Inch (mm) |
|--------------|--------------|-----------|-------------|-------------------------------|--------------------------|------------------|--------------|-------------------|------------------|------------------|
| 48530        | .4 (298)     | 12,000    | 81 dB(A)    | 21 (595)                      | 1/4 (6)                  | 1/4" NPT         | 1/4"-20 Male | 1.2 (0.5)         | 7-3/8 (187)      | 3-1/8 (79)       |
| 48531        | .4 (298)     | 15,000    | 80 dB(A)    | 21 (595)                      | 1/4 (6)                  | 1/4" NPT         | 1/4"-20 Male | 1.2 (0.5)         | 7-3/8 (187)      | 3-1/8 (79)       |
| 48532        | .4 (298)     | 20,000    | 83 dB(A)    | 21 (595)                      | 1/4 (6)                  | 1/4" NPT         | 1/4"-20 Male | 1.2 (0.5)         | 7-3/8 (187)      | 3-1/8 (79)       |

Tune-Up Kit: No. 96541 (page 267) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

#### Right Angle, .55 hp, Gearless, Rear Exhaust

- Includes 51347 Locking-Type Pad (3" diameter).
- Removable side handle.
- Optional safety-lock lever available.
- Tool combines top efficiency with great value.

**Model 52557** 15,000 RPM, Extended Muffler

**Model 52558** 15,000 RPM, Standard Muffler



Model 52557



Model 52557

| Model Number | Motor hp (W) | Motor RPM | Sound Level | Maximum Air Flow SCFM (L/Min) | Hose I.D. Size Inch (mm) | Air Inlet Thread | Tool Thread  | Weight Pound (kg) | Length Inch (mm) | Height Inch (mm) |
|--------------|--------------|-----------|-------------|-------------------------------|--------------------------|------------------|--------------|-------------------|------------------|------------------|
| 52557        | .55 (410)    | 15,000    | 75 dB(A)    | 33 (934)                      | 3/8 (10)                 | 1/4" NPT         | 3/8"-24 Male | 1.9 (0.8)         | 6 (152)          | 3-7/8 (98)       |
| 52558        | .55 (410)    | 15,000    | 84 dB(A)    | 33 (934)                      | 3/8 (10)                 | 1/4" NPT         | 3/8"-24 Male | 1.9 (0.8)         | 4-1/2 (114)      | 3-7/8 (98)       |

Tune-Up Kit: No. 96522 (page 267) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

#### 7° Offset, .7 hp, Gearless

- Includes 51347 Locking-Type Pad (3" diameter).
- Removable side handle.

**Model 52410** 15,000 RPM, Front Exhaust

**Model 52412** 20,000 RPM, Front Exhaust

**Model 52413** 15,000 RPM, Rear Exhaust

**Model 52415** 20,000 RPM, Rear Exhaust

- Extended muffler design (52413 and 52415 only).



Model 52412



Model 52412

| Model Number | Motor hp (W) | Motor RPM | Sound Level | Maximum Air Flow SCFM (L/Min) | Hose I.D. Size Inch (mm) | Air Inlet Thread | Tool Thread  | Weight Pound (kg) | Length Inch (mm) | Height Inch (mm) |
|--------------|--------------|-----------|-------------|-------------------------------|--------------------------|------------------|--------------|-------------------|------------------|------------------|
| 52410        | .7 (522)     | 15,000    | 92 dB(A)    | 32 (906)                      | 3/8 (10)                 | 1/4" NPT         | 3/8"-24 Male | 2.0 (0.9)         | 6 (152)          | 5-1/2 (140)      |
| 52412        | .7 (522)     | 20,000    | 90 dB(A)    | 36 (1,019)                    | 3/8 (10)                 | 1/4" NPT         | 3/8"-24 Male | 2.0 (0.9)         | 6 (152)          | 5-1/2 (140)      |
| 52413        | .7 (522)     | 15,000    | 74 dB(A)    | 32 (906)                      | 3/8 (10)                 | 1/4" NPT         | 3/8"-24 Male | 2.3 (1.0)         | 8-1/8 (206)      | 5-1/2 (140)      |
| 52415        | .7 (522)     | 20,000    | 74 dB(A)    | 35 (991)                      | 3/8 (10)                 | 1/4" NPT         | 3/8"-24 Male | 2.3 (1.0)         | 8-1/8 (206)      | 5-1/2 (140)      |

Tune-Up Kit: No. 96045 (page 267) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

DISC SANDERS