

# 7" Dia. Disc Sanders

## 1.3 hp Model, Right Angle



DISC PADS  
PAGE 242

ACCESSORIES  
PAGE 222

*Lightweight Tool Delivers BIG Power and Performance*

FOR ABRASIVE DISCS  
7" (178 mm) diameter  
SEE PAGE 280

- *Ideal for grinding sheet metal, composites and carbon fiber. Perfect for large surfaces.*
- *Also utilized for sanding and deburring metal parts.*
- *Great for surface conditioning, plus removing paint, rust and mill finish.*

- Includes 51151 Backing Pad, 7" (178 mm) diameter, and flange.
- Tool accepts optional 7" (178 mm) diameter Abrasive Discs with 7/8" (22 mm) center hole.
- Quiet, robust air motor is governor-controlled to maintain consistent RPM under load.
- Convenient Spindle Lock allows quick and easy changing of backing pad or abrasive.
- "Wick Lube" System extends gear life with simple lubrication.
- Vibration dampening side handle is removable for left or right hand use.
- Exhaust system rotates 360° to ensure exhaust is always directed away from operator.
- Solid cast aluminum construction.
- Insulated throttle handle reduces cold air transmission to hand. Throttle Handle position is adjustable.



Model 52657

DISC SANDERS

### 5/8"-11 Spindle Thread Models

**Model 52657 6,000 RPM**

**Model 52802 7,200 RPM**

**Model 53868 8,500 RPM**

### M14x2 Spindle Thread Models

**Model 52656 6,000 RPM**

**Model 53869 8,500 RPM**



Model 52657

All models include 95848 Gear Oil and 95541 Gear Oil Gun. Simple lubrication extends gear life.

*See page 90 for VACUUM Model!*

| Model Number | Motor hp (W) | Motor RPM | Sound Level | Maximum Air Flow SCFM (L/Min) | Hose I.D. Size Inch (mm) | Air Inlet Thread | Tool Thread  | Weight Pound (kg) | Length Inch (mm) | Height Inch (mm) |
|--------------|--------------|-----------|-------------|-------------------------------|--------------------------|------------------|--------------|-------------------|------------------|------------------|
| 52657        | 1.3 (969)    | 6,000     | 76 dB(A)    | 40 (1,138)                    | 3/8 (10)                 | 3/8" NPT         | 5/8"-11 Male | 4.5 (2.0)         | 10 (255)         | 3-9/16 (90)      |
| 52802        | 1.3 (969)    | 7,200     | 78 dB(A)    | 40 (1,138)                    | 3/8 (10)                 | 3/8" NPT         | 5/8"-11 Male | 4.5 (2.0)         | 10 (255)         | 3-9/16 (90)      |
| 53868        | 1.3 (969)    | 8,500     | 77 dB(A)    | 40 (1,138)                    | 3/8 (10)                 | 3/8" NPT         | 5/8"-11 Male | 4.5 (2.0)         | 10 (255)         | 3-9/16 (90)      |
| 52656        | 1.3 (969)    | 6,000     | 76 dB(A)    | 40 (1,138)                    | 3/8 (10)                 | 3/8" NPT         | M14x2        | 4.5 (2.0)         | 10 (255)         | 3-9/16 (90)      |
| 53869        | 1.3 (969)    | 8,500     | 79 dB(A)    | 40 (1,138)                    | 3/8 (10)                 | 3/8" NPT         | M14x2        | 4.5 (2.0)         | 10 (255)         | 3-9/16 (90)      |

**Tune-Up Kit: No. 96100** (page 267) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)