3" Dia. Vacuum Disc Sanders

VAC SHROUDS PAGE 221 DISC PADS PAGE 242

FOR ABRASIVE DISCS

3" (76 mm) diameter SEE PAGE 279

.4 hp, Right Angle Models, Rear Exhaust

Material Removal with Source Capture

Self-Generated Vacuum Models

- Flexible, non-marring Vacuum Shroud allows capture of dust, debris and contaminants (including Hexavalent Chromium).
- Vacuum Shroud constructed of high-quality clear urethane. Unique "view port" allows operator to see edge of sanding disc, and offers optimum view of work surface.
- For use on non-metallic materials, such as fiberglass and composites.
- Utilizes tool's exhaust to create strong vacuum suction. 1" (25 mm) diameter vacuum port ready for connection to optional portable self-contained dust collection system (see page 219).
- Each model includes 51346 Backing Pad, for 3" (76 mm) diameter locking-type abrasive discs.
- "Wick Lube" system extends gear life with simple lubrication.



Shroud angle ensures ideal contact of abrasive to work surface.



Self-Generated Vacuum, Trimmed Shroud

Model 50210 Trimmed Shroud, 15,000 RPM


 Trimmed Shroud height of 1" (25 mm) accommodates 3" (76 mm) diameter locking-type abrasive discs (sold separately).

Model	Motor	Motor	Sound	Maximum Air Flow	Hose I.D. Size	Air Inlet	Tool	Weight	Length	Height
Number	hp (W)	RPM	Level	SCFM (L/Min)	Inch (mm)	Thread	Thread	Pound (kg)	Inch (mm)	Inch (mm)
50210	.4 (298)	15,000	86 dB(A)	21 (595)	1/4 (6)	1/4" NPT	1/4"-20 Male	1.7 (0.7)	9-3/4 (249)	

Tune-Up Kit: No. 96179 (page 267) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

Model 50570 Standard Shroud, 15,000 RPM

- Standard Shroud height of 1-1/2" (38 mm) accommodates 2" (51 mm) diameter bristle-type discs (sold separately).
- Standard Shroud may also be trimmed for accommodating 3" (76 mm) locking-type coated abrasive and non-woven nylon discs.





Self-Generated Vacuum, Standard Shroud

Model	Motor	Motor	Sound	Maximum Air Flow	Hose I.D. Size	Air Inlet	Tool	Weight	Length	Height
Number	hp (W)	RPM	Level	SCFM (L/Min)	Inch (mm)	Thread	Thread	Pound (kg)	Inch (mm)	Inch (mm)
50570	.4 (298)	15,000	86 dB(A)	21 (595)	1/4 (6)	1/4" NPT	1/4"-20 Male	1.7 (0.7)	9-3/4 (249)	

Tune-Up Kit: No. 96179 (page 267) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)