

Depressed Center Wheel Grinders

1.3 hp, Right Angle, 4"-5" Diameter



DYNASWIVEL®
PAGE 223

COUPLER/PLUG
PAGE 228

For Fast Weld and Stock Removal, Rust and Scale Removal, Heavy Deburring

FOR TYPE 27 REINFORCED
DEPRESSED CTR. WHEELS
4"-5" Dia. (102 mm-127 mm)
SEE PAGE 281

4" (102 mm) Diameter, 13,500 RPM Model

Model 52630

13,500 RPM, 3/8"-24 Spindle Thread

- Tool accepts optional 4" (102 mm) diameter Type 27 Reinforced Depressed Center Wheels with 5/8" (16 mm) center hole (wheel width of 1/8" to 1/4").

Vibration Dampening
Side Handle included!
(All models on page)



Type 27 Wheel
Sold Separately

4-1/2" (114 mm) Diameter, 12,000 RPM Models

- Tool accepts optional 4-1/2" (114 mm) diameter Type 27 Reinforced Depressed Center Wheels with 7/8" (22 mm) center hole (wheel width of 1/8" to 1/4").
- Tool also accepts optional 4-1/2" (114 mm) diameter Abrasive Flap Discs (flanging sold separately).

Model 52632 5/8"-11 Spindle Thread

Model 52638 M14x2 Spindle Thread



Type 27 Wheel
Sold Separately

Optional Backup Flange

- For mounting high-profile Abrasive Flap Disc with 7/8" center hole.

53697 – for 5/8"-11 Models.

53630 – for M14x2 Models.



5" (127 mm) Diameter, 12,000 RPM Models

- Tool accepts optional 5" (127 mm) diameter Type 27 Reinforced Depressed Center Wheels with 7/8" (22 mm) center hole (wheel width of 1/8" to 1/4").
- Tool also accepts optional 5" (127 mm) diameter Abrasive Flap Discs (flanging sold separately).

Model 52633 5/8"-11 Spindle Thread

Model 52639 M14x2 Spindle Thread



Type 27 Wheel
Sold Separately

IMPORTANT: Speed of tool must not exceed maximum operating speed of accessory. Never mount non-reinforced grinding wheels. Always wear eye, face & body protection.

| Model Number | Motor hp (W) | Motor RPM | Sound Level | Maximum Air Flow SCFM (L/Min) | Hose I.D. Size Inch (mm) | Air Inlet Thread | Tool Thread | Weight Pound (kg) | Length Inch (mm) | Height Inch (mm) |
|--------------|--------------|-----------|-------------|-------------------------------|--------------------------|------------------|--------------|-------------------|------------------|------------------|
| 52630 | 1.3 (970) | 13,500 | 81 dB(A) | 43 (1,218) | 3/8 (10) | 3/8" NPT | 3/8"-24 Male | 4.8 (2.2) | 10 (254) | 3.4 (86) |
| 52632 | 1.3 (970) | 12,000 | 79 dB(A) | 43 (1,218) | 3/8 (10) | 3/8" NPT | 5/8"-11 Male | 5.1 (2.3) | 10 (254) | 3.8 (96) |
| 52633 | 1.3 (970) | 12,000 | 79 dB(A) | 43 (1,218) | 3/8 (10) | 3/8" NPT | 5/8"-11 Male | 5.4 (2.5) | 10 (254) | 3.8 (96) |
| 52638 | 1.3 (970) | 12,000 | 80 dB(A) | 43 (1,218) | 3/8 (10) | 3/8" NPT | M14x2 Male | 5.1 (2.3) | 10 (254) | 3.8 (96) |
| 52639 | 1.3 (970) | 12,000 | 80 dB(A) | 43 (1,218) | 3/8 (10) | 3/8" NPT | M14x2 Male | 5.4 (2.5) | 10 (254) | 3.8 (96) |

Tune-Up Kit: No. 96100 (page 267) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

GRINDERS