



# OXIDE REMOVAL DISCS

Reorder No. EUR09.10

*For use with the Dynastraight® or the Dynabrade Disc Sander with Speed Regulator.  
Available with centre hole, shaft and Locking-Type system.*

## OXIDE REMOVAL BLACK DISCS

Conforms to work area,  
ideal for use in Automotive for paint removal.



DIMENSION	ATTACHMENT TYPE	P/N	QTY/BOX
75 mm x 13 mm	Locking-Type	72963	10
75 mm x 13 mm	Hole 13 mm	72962	10
100 mm x 13 mm	Hole 13 mm	72965	10
150 mm x 13 mm	Hole 13 mm	72967	10
75 mm x 13 mm	Shaft 6 mm	72964	10
100 mm x 13 mm	Shaft 6 mm	72966	10
150 mm x 13 mm	Shaft 8 mm	72968	10
100 mm x 25 mm	Shaft 6 mm	72969	10
150 mm x 25 mm	Shaft 8 mm	72970	10

## OXIDE REMOVAL ORANGE DISCS

Made of rigid open web  
that is aggressive and long-lasting.



DIMENSION	ATTACHMENT TYPE	P/N	QTY/BOX
75 mm x 13 mm	Locking-Type	72973	10
75 mm x 13 mm	Hole 13 mm	72971	10
100 mm x 13 mm	Hole 13 mm	72974	10
150 mm x 13 mm	Hole 13 mm	72976	10
75 mm x 13 mm	Shaft 6 mm	72972	10
100 mm x 13 mm	Shaft 6 mm	72975	10
150 mm x 13 mm	Shaft 8 mm	72977	10
100 mm x 25 mm	Shaft 6 mm	72978	10
150 mm x 25 mm	Shaft 8 mm	72979	10

## APPLICATIONS & MARKETS

- Aggressively removes paint and rust from welding seams, undercoating, seam-sealers and stone guards.
- Applications in trunk beds and doorjambs for removing sealant.
- Used to remove oxidation from tyre rims and rust from brake assemblies.
- Removing weld blueing and oxide on stainless steel containers.
- Removing of old gasket material on cylinder heads of diesel engines.
- For cleaning welds and light coating removal.
- Ideal for work on stainless steel, standard or alloyed steel, aluminum, titanium, nonferrous materials and alloys, fibreglass, plastic, stone or wood.
- Often used in the Automotive repair industry.



## FEATURES & BENEFITS

- Oxide Removal Discs available in centre hole, shaft or Locking-Type system.
- Strong 3-dimensional synthetic fibre construction, very open, with extra coarse silicon carbide.
- High resistance to clogging and fast removal.
- Long lifetime, safer than wire brushes.
- Conforms to work piece and does not damage the work pieces.
- Allows access to difficult areas like wheel wells and under-carriage.
- Fast removal of rust and paint without base material removal.



DYNABRADE EUROPE S.à.r.l.

ZONE ARTISANALE • L-5485 WORMELDANGE-HAUT • LUXEMBOURG • TEL.: +352 768 494 1 • FAX: +352 768 495 • [SALES@DYNABRADE.LU](mailto:SALES@DYNABRADE.LU)