



DISCHI SURFACE CONDITIONING

Codice n° EUR09.20

Da usare con Dynabrade Disc Sanders.

DISCHI SURFACE CONDITIONING CON ATTACCO VELCRO



DIMENSION	ATTACHMENT TYPE	GRIT	P/N	QTY/BOX
115 mm	Velcro	Coarse	72950	10
115 mm	Velcro	Medium	72951	10
115 mm	Velcro	Very Fine	72952	10

DISCHI SURFACE CONDITIONING LOCKING-TYPE



DIMENSION	ATTACHMENT TYPE	GRIT	P/N	QTY/BOX
50 mm	Locking-Type	Coarse	72953	50
50 mm	Locking-Type	Medium	72954	50
50 mm	Locking-Type	Very Fine	72955	50
75 mm	Locking-Type	Coarse	72956	25
75 mm	Locking-Type	Medium	72957	25
75 mm	Locking-Type	Very Fine	72958	25

Disponibile in diametro 100 mm su richiesta

PLATORELLI LOCKING-TYPE

DIMENSION	ATTACHMENT TYPE	DENSITY	P/N	QTY
50 mm	Locking-Type (1/4")	Medium	51344	per pezzo
50 mm	Locking-Type (3/8")	Medium	51345	per pezzo
75 mm	Locking-Type (1/4")	Medium	51346	per pezzo
75 mm	Locking-Type (3/8")	Medium	51347	per pezzo

APPLICAZIONI E MERCATI

- Mascheratura dei segni superficiali su pannelli auto.
- Finitura decorativa, decapaggio, pulitura di cordoni di saldatura.
- Rimozione di piccole bave.
- Per uso su acciaio inox, alluminio, titanio, leghe, fibra di vetro e plastica.



CARATTERISTICHE E BENEFICI

- Dischi in tessuto non tessuto abrasivo con attacco Velcro o sistema Locking-Type.
- Struttura in tessuto non tessuto poco intasante.
- Cambio rapido, attacco sicuro e centrato del disco grazie al sistema Locking-Type.
- Minori tempi morti.

