

# Air Supply Accessories

## Cost-Effective Solutions for Air Systems

### Swivel Air Line Hoses

- Eliminates kinking, fittings swivel 360° for easy use.
- Tough, flexible and lightweight.



Hose I.D. Inch (mm)	Hose O.D. Inch (mm)	Part Number	Female Fittings	Male Fittings	Length
5/32 (4)	1/4 (6)	96217	1 (1/4")	1 (1/4")	3 ft. (910 mm)
		96218	1 (1/4")	1 (1/8")	3 ft. (910 mm)
		96219	1 (1/4")	1 (1/4")	6 ft. (1.8 m)
		96220	1 (1/4")	1 (1/8")	6 ft. (1.8 m)
		96221	0*	0*	Specify Length
1/4 (6)	3/8 (10)	96222	1 (1/4")	1 (1/4")	3 ft. (910 mm)
		96223	1 (1/4")	1 (1/4")	6 ft. (1.8 m)
		96224	0*	0*	Specify Length

\* Order fittings separately, if desired

### Press-On Fittings

For Use With	Part Number	Description
1/4" (6 mm) Hose	96225	1/4" NPT Female
	96226	1/4" NPT Male
	96227	1/8" NPT Male
3/8" (10 mm) Hose	96228	1/4" NPT Female
	96229	1/4" NPT Male



### Reusable Fittings

- No tools required, simply insert fittings into air hose.

For Use With	Part Number	Description
8 mm Dia. Hose	94897	1/4" NPT Male



### Speed Control Dial

- Connects directly to air tool.

Hose and Tool Connections	Part Number	Air Flow Range SCFM (LPM)
1/4" NPT	95745	Up to 25 (708)
3/8" NPT	95746	Up to 26-45 (736-1,274)



### Lightweight 8 mm I.D. Air Hose Assembly

- Use this assembly to connect an FRL to a Dynabrade tool for optimum results.
- Air line is 66% lighter than conventional PVC and rubber hoses.
- Reinforced hose is made of an anti-abrasive PU and thermoplastic rubber compound.
- High flexibility and narrow bending radius of hose prevent choking.
- High resistance to ozone, hydrocarbons, fats, oils, and slightly aggressive chemical products.



Length	Part Number	Hose O.D.	Female Fittings	Male Fittings
5 ft. (1.5 m)	94874	12.7 mm	0	2
	94863	12.7 mm	1	1
12 ft. (3.7 m)	94851	12.7 mm	0	2
	94852	12.7 mm	1	1
25 ft. (7.6 m)	94876	12.7 mm	0	2
	94892	12.7 mm	1	1
328 ft. (100 m)	94860	12.7 mm	0	0

### Flexible Air Line Assemblies



Hose I.D. Inch (mm)	Part Number	Female Fittings	Male Fittings	Length
1/4 (6)	95361	1	1	5 ft. (1.5 m)
	95580	1	1	28" (711 mm)
	95807	0	0	Specify Length
	95938	1	1	Specify Length
3/8 (10)	11292	0	2	8 ft. (2.4 m)
1/2 (13)	95870	1	1	5 ft. (1.5 m)

# Plugs

## Ported Design to Prevent Starving of the Air Tool

- Durable zinc-plated steel construction.
- Provides up to twice the air flow compared to standard plug design.



Body Size	Part Number	Thread Size (NPT)	Air Flow Range SCFM (LPM)
1/4"	95675	1/4" Male	Up to 74 (2,095)
	95677	1/4" Female	
	96005	3/8" Male	
3/8"	98263	3/8" Male	Up to 138 (3,900)
	98264	3/8" Female	
1/2"	98271	1/2" Male	Up to 138 (3,900)
	98272	1/2" Female	