

Effective June, 2015

Please Note the Following:

Dynabrade, Inc. only distributes this product as a reseller and is not the manufacturer of this product you have purchased. The MSDS/SDS document included with this product is prepared and supplied by the original manufacturer and is the most current documentation made available to Dynabrade, Inc. at the time of shipping this product. Although Dynabrade, Inc. makes every reasonable effort to ensure the accuracy and reliability of the information contained in the MSDS/SDS document, Dynabrade, Inc. makes no warranty, express or implied, with respect to the accuracy or reliability of such information, nor will Dynabrade, Inc. assume any liability for any loss or damage arising out of the use of such information including without limitation direct or indirect losses or expenses. All questions regarding this product should be directed to the original manufacturer, as listed in Section 1 of the MSDS/SDS document. It is your responsibility as the purchaser of this product to keep up to date with your MSDS/SDS document by periodically checking in with the original manufacturer for updates.

Dynabrade Part Number:

95542 **Dynabrade Grease**

• 10 oz. (283.5 g)



Email: customer.service@dynabrade.com

Visit Our Website: Dynabrade.com

8989 Sheridan Drive Clarence, NY 14031-1419 USA Telephone: (716) 631-0100 Fax: 716-631-2073

International Fax: 716-631-2524

DYNABRADE EUROPE S.àr.I.

Zone Artisanale Op Tomm 6 L-5485 Wormeldange-Haut Luxemboura

Telephone: +352 768 494 1 Fax: +352 768 495

DYNABRADE INDIA ABRASIVE POWER TOOLS Pvt Ltd.

EL-54. TTC Industrial Area, M.I.D.C. Mahape Electronic Zone, Navi Mumbai - 400705 Maharashtra India

Telephone: +91 22 2763 2226 Fax: +91 22 2763 2228









SAFETY DATA SHEET

No. 630-A/AA/AAA/2

Section 1. Identification

: No. 630-A/AA/AAA/2 **GHS** product identifier

Other means of identification

: Not available.

Product type : Solid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Petroleum lubricating grease

Area of application : Industrial applications.

: LUBRIPLATE® Lubricants Co. Supplier/Manufacturer

> 129 Lockwood St. Newark, NJ 07105

Telephone no.: 1-973-589-9150

e-mail address of person responsible for this SDS

: SDS@lubriplate.com

Emergency telephone number (with hours of

operation)

: CHEM-TEL 1-800-255-3924 (24 hour)

Section 2. Hazards identification

OSHA/HCS status This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the substance or mixture : Not classified.

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 13.1%

GHS label elements

: No signal word. Signal word

Hazard statements : No known significant effects or critical hazards.

Precautionary statements

Prevention : Not applicable. : Not applicable. Response : Not applicable. **Storage Disposal** : Not applicable.

Supplemental label

elements

: Avoid contact with skin and clothing. Wash thoroughly after handling.

Hazards not otherwise

classified

: Defatting to the skin. Prolonged or repeated contact may dry skin and cause irritation.

Date of issue/Date of revision : 11/24/2014 Date of previous issue : No previous validation Version :1 1/12

Section 3. Composition/information on ingredients

Substance/mixture
Other means of

identification

: Mixture: Not available.

CAS number/other identifiers

CAS number : Not applicable. **Product code** : Not available.

Ingredient name	Other names	%	CAS number
Distillates (petroleum), hydrotreated heavy naphthenic	Distillates (petroleum), hydrotreated heavy naphthenic	60-100	64742-52-5
Distillates (petroleum), hydrotreated light naphthenic	Distillates (petroleum), hydrotreated light naphthenic	30-60	64742-53-6
zinc oxide	zinc oxide	1-5	1314-13-2
tris(dipentyldithiocarbamato-S,S')antimony	tris (dipentyldithiocarbamato-S, S')antimony	1-5	15890-25-2

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.

Ingestion

: Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : N

: No known significant effects or critical hazards.

Inhalation

: Exposure to decomposition products may cause a health hazard. Serious effects may

be delayed following exposure.

Skin contact

: Defatting to the skin. May cause skin dryness and irritation.

Ingestion

: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No specific data. **Inhalation** : No specific data.

Skin contact

: Adverse symptoms may include the following:

irritation dryness cracking

Date of issue/Date of revision

: 11/24/2014 Date of previous issue

: No previous validation

Version :1

2/12

Section 4. First aid measures

Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. Notes to physician

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: Use dry chemical, CO₂, alcohol-resistant foam or water spray (fog).

Unsuitable extinguishing media

: Do not use water jet.

Specific hazards arising from the chemical

: No specific fire or explosion hazard.

Hazardous thermal decomposition products : Decomposition products may include the following materials: carbon dioxide

carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Date of issue/Date of revision : 11/24/2014 Date of previous issue : No previous validation Version :1 3/12

Section 6. Accidental release measures

Large spill

: Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Advice on general occupational hygiene

- : Put on appropriate personal protective equipment (see Section 8).
- : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy naphthenic	ACGIH TLV (United States, 6/2013). TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2013). TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist
Distillates (petroleum), hydrotreated light naphthenic	OSHA PEL (United States, 2/2013). TWA: 5 mg/m³ 8 hours. ACGIH TLV (United States, 6/2013). TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction
	NIOSH REL (United States, 10/2013). TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist OSHA PEL (United States, 2/2013). TWA: 5 mg/m³ 8 hours.
zinc oxide	NIOSH REL (United States, 10/2013). CEIL: 15 mg/m³ Form: Dust TWA: 5 mg/m³ 10 hours. Form: Dust and fumes
	STEL: 10 mg/m³ 15 minutes. Form: Fume OSHA PEL 1989 (United States, 3/1989). TWA: 5 mg/m³ 8 hours. Form: Fume STEL: 10 mg/m³ 15 minutes. Form: Fume TWA: 5 mg/m³ 8 hours. Form: Respirable
	fraction TWA: 10 mg/m³ 8 hours. Form: Total dust OSHA PEL (United States, 2/2013). TWA: 5 mg/m³ 8 hours. Form: Fume TWA: 5 mg/m³ 8 hours. Form: Respirable fraction

Date of issue/Date of revision : 11/24/2014 Date of previous issue : No previous validation Version :1 4/12

Section 8. Exposure controls/personal protection

TWA: 15 mg/m³ 8 hours. Form: Total dust

ACGIH TLV (United States, 6/2013). TWA: 2 mg/m³ 8 hours. Form: Respirable

fraction

STEL: 10 mg/m³ 15 minutes. Form:

Respirable fraction

ACGIH TLV (United States, 6/2013). TWA: 0.5 mg/m³, (as Sb) 8 hours.

OSHA PEL 1989 (United States, 3/1989).

TWA: 0.5 mg/m³, (as Sb) 8 hours.

OSHA PEL (United States, 2/2013).

TWA: 0.5 mg/m³, (as Sb) 8 hours.

NIOSH REL (United States, 10/2013).

TWA: 0.5 mg/m³, (as Sb) 10 hours.

Appropriate engineering controls

tris(dipentyldithiocarbamato-S,S')antimony

Environmental exposure controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Date of issue/Date of revision : 11/24/2014 Date of previous issue : No previous validation Version : 1 5/12

Section 9. Physical and chemical properties

Appearance

Physical state : Solid. [grease]
Color : Off-white.
Odor : Mineral oil.
Odor threshold : Not available.
pH : Not available.
Melting point : Not available.
Boiling point : >288°C (>550.4°F)

Flash point : Open cup: 204°C (399.2°F) [Cleveland.]

Evaporation rate : <0.01 (butyl acetate = 1)

Flammability (solid, gas) : Not available.

Lower and upper explosive (flammable) limits : Lower: 0.9% Upper: 7%

Vapor pressure : <0.0013 kPa (<0.01 mm Hg) [room temperature]

Vapor density : >5 [Air = 1]
Relative density : 0.95 [Water = 1]

Solubility : Insoluble in the following materials: cold water and hot water.

Solubility in water : Not available.

Partition coefficient: n- : Not available.

octanol/water

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

SADT : Not available.

Viscosity : Kinematic (40°C (104°F)): 1.35 to 1.51 cm²/s (135 to 151 cSt)

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Under normal conditions of storage and use, hazardous polymerization will not occur.

Conditions to avoid : Keep away from heat, sparks and flame. Keep away from all sources of ignition.

Incompatible materials: Reactive or incompatible with the following materials: oxidizing materials and acids.

Incompatibility: Chlorine

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Date of issue/Date of revision : 11/24/2014 Date of previous issue : No previous validation Version :1 6/12

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), hydrotreated heavy naphthenic	LD50 Oral	Rat	>5000 mg/kg	-
Distillates (petroleum), hydrotreated light naphthenic	LD50 Oral	Rat	>5000 mg/kg	-
tris(dipentyldithiocarbamato- S,S')antimony	LD50 Dermal	Rabbit	>16000 mg/kg	-
, ,	LD50 Oral	Rat	>16400 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Distillates (petroleum), hydrotreated heavy naphthenic	Skin - Severe irritant	Rabbit	-	500 milligrams	-
zinc oxide	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Conclusion/Summary

: The mineral oils in the product contain < 3% DMSO extract (IP 346).

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Name	Result
Distillates (petroleum), hydrotreated heavy naphthenic	ASPIRATION HAZARD - Category 1
Distillates (petroleum), hydrotreated light naphthenic	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

Date of issue/Date of revision

: Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects

Eye contact Inhalation

: No known significant effects or critical hazards.

Date of previous issue

: 11/24/2014

: Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

: No previous validation

Version :1

7/12

be delayed following exposure.

United States

No. 630-A/AA/AAA/2

Section 11. Toxicological information

Skin contact: Defatting to the skin. May cause skin dryness and irritation.

Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation dryness cracking

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

effects

: Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or

dermatitis.

Carcinogenicity
 No known significant effects or critical hazards.
 Mutagenicity
 No known significant effects or critical hazards.
 Teratogenicity
 No known significant effects or critical hazards.
 Developmental effects
 No known significant effects or critical hazards.
 Fertility effects
 No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
	64701.2 mg/kg 194.1 mg/l

Section 12. Ecological information

Toxicity

Section 12. Ecological information

Product/ingredient name	Result	Species	Exposure
zinc oxide	Acute EC50 0.042 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours
	Acute LC50 98 μg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 1.1 ppm Fresh water Chronic NOEC 0.017 mg/l Fresh water	Fish - Oncorhynchus mykiss Algae - Pseudokirchneriella subcapitata - Exponential growth phase	96 hours 72 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
zinc oxide	-	60960	high

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	IMDG	IATA
UN number	Not regulated.	UN3077	UN3077
UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (zinc oxide, tris (dipentyldithiocarbamato-S,S') antimony). Marine pollutant (zinc oxide, tris (dipentyldithiocarbamato-S,S') antimony)	Environmentally hazardous substance, solid, n.o.s. (zinc oxide, tris (dipentyldithiocarbamato-S,S') antimony)

Date of issue/Date of revision: 11/24/2014Date of previous issue: No previous validationVersion: 1

Section 14. Transport information

Transport hazard class(es)	-	9	9
Packing group	-	III	III
Environmental hazards	No.	Yes.	Yes.
Additional information		The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. Emergency schedules (EmS) F-A, S-F Special provisions 274, 335, 966, 967	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. Passenger and Cargo Aircraft Quantity limitation: 400 kg Packaging instructions: 956 Cargo Aircraft Only Quantity limitation: 400 kg Packaging instructions: 956 Limited Quantities - Passenger Aircraft Quantity limitation: 30 kg Packaging instructions: Y956 Special provisions A97, A158, A179

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according: Not available.

to Annex II of MARPOL 73/78 and the IBC Code

Section 15. Regulatory information

U.S. Federal regulations

: United States inventory (TSCA 8b): All components are listed or exempted. Clean Water Act (CWA) 307: zinc oxide; tris(dipentyldithiocarbamato-S,S')antimony

: Listed

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)**

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602 **Class II Substances**

: Not listed

DEA List I Chemicals

: Not listed

(Precursor Chemicals)

: Not listed

DEA List II Chemicals (Essential Chemicals)

SARA 302/304

Composition/information on ingredients

No products were found.

Date of issue/Date of revision : 11/24/2014 Date of previous issue : No previous validation Version :1 10/12 No. 630-A/AA/AAA/2

Section 15. Regulatory information

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : Immediate (acute) health hazard

Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Distillates (petroleum), hydrotreated heavy naphthenic	60-100	No.	No.	No.	Yes.	No.
Distillates (petroleum), hydrotreated light naphthenic	30-60	No.	No.	No.	Yes.	No.
zinc oxide	1-5	No.	No.	No.	Yes.	No.
tris(dipentyldithiocarbamato-S,S') antimony	1-5	No.	No.	No.	Yes.	No.

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	1	1314-13-2 15890-25-2	1-5 1-5
Supplier notification		1314-13-2 15890-25-2	1-5 1-5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: MINERAL OIL, PETROLEUM DISTILLATES,

HYDROTREATED LIGHT NAPHTHENIC; ZINC OXIDE FUME

New York : None of the components are listed.

New Jersey : The following components are listed: MINERAL OIL (HIGHLY REFINED); OIL MIST, MINERAL; MINERAL OIL (HIGHLY REFINED); OIL MIST, MINERAL; ZINC OXIDE;

MITIMONY compounds

ANTIMONY compounds

Pennsylvania : The following components are listed: ZINC OXIDE (ZNO); ANTIMONY COMPOUNDS

California Prop. 65

None of the components are listed.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Date of issue/Date of revision : 11/24/2014 Date of previous issue : No previous validation Version : 1 11/12

Section 16. Other information



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

History

Date of issue/Date of

revision

: 11/24/2014

Date of previous issue

: No previous validation

Version
Prepared by

: 1 : IHS

Key to abbreviations

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

References

: HCS (U.S.A.)- Hazard Communication Standard

International transport regulations

▼ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.